



XGA	5,500 ANSI	3,000,000:1
WUXGA	5,000 ANSI	3,000,000:1

Spec.		
모델명	SX755 (HLD755X)	SU750 (HLD750U)
<b>Optical Spec.</b>		
밝기(ANSI)	5500	5000
Display Technology	3LCD	
명암비(Contract Ratio)	3,000,000:1 (Bright mode)	
해상도(Resolution)	XGA (1024x768)	WUXGA (1920 X 1200)
Light Source	HLD LASER	
Light Source Time	25,000H	
Aspect Ratio	4:3	16:10
<b>Projection Lens</b>		
Zoom/Focus	Manual	
Zoom Ratio	1.6x optics	
Throw Ratio	70" @1.55m; 1.09~1.74 : 1	70" @1.64m; 1.09~1.78 : 1
F	F 1.65~2.25	
f	f= 18.20~29.38mm	
Screen Size	0.894~11.184m(40"~300")	0.928~11.605m (40"~300")
Lens Shift	수직V : ±32% 수평H : ±8%	수직V : ±38% 수평H : ±8%
<b>Generic Spec.</b>		
Speaker	2*10W	
Scanning Frequency	Hsync Frequency 15~100KHz / Vsync Frequency 48~85Hz	
Computer Signal Input	PC, VGA, SVGA, XGA, SXGA, WXGA, UXGA, WUXGA, Mac	
Video Compatibility	PAL, SECAM, NTSC 4.43, PAL-M, PAL-N, 480i, 480p, 576i, 576p, 720p, 1080p and 1080i	
Power Consumption	450W	
ECO Standby Mode	<0.5W	
Network standby	<2W	
Keystone Correction	V: ±30°(auto+manual), H: ±15° (manual), Pincushion/Barrel Correction, Corner Keystone	V: ±30°(auto+manual), H: ±15°(manual), Corner Keystone
OSD(Languages)	26 languages: English, German, French, Italian, Spanish, Polish, Swedish, Dutch, Portugese, Japanese, Simplified Chinese, Traditional Chinese, Korea, Russian, Arabic, Turkish, Finnish, Norwegian, Danish, Indonesian, Hungarian, Czech,	
Input Terminals	2 X 15-pin Mini D-sub(RGB) 1 X D-sub15 (Component) 2 X HDMI 1 X S-Video 1 X RCA(Composite) 1 X Stereo mini jack(Audio) 2 X 2RCA(L/R) Audio	
Output Terminals	1 X 15-pin Mini D-sub 1 X Stereo mini jack(Audio)	
Other Terminals	RS-232x1, RJ45 x1(control), Micro-USBx1(for up-grade)	
<b>Mechanical Spec.</b>		
Power Requirement	AC 100 – 240 V ,.. 50-60 Hz	
Net. Weight(KG)	10 kg	
Max Dimensions	460(W) x 335(D) x 143(H) mm	
<b>Accessories</b>		
Standard	Power cord, VGA cable, Remote control	



## ■ 투사거리표

### XGA(4:3)

인치	W (mm)	H (mm)	최단거리 (화면최대)	최장거리 (화면최소)
30	609,6	457,2	662	1093
40	812,8	609,6	894	1467
60	1219,2	914,4	1357	2214
70	1422,4	1066,8	1588	2588
80	1625,6	1219,2	1819	2962
90	1828,8	1371,6	2051	3335
100	2032	1524	2282	3709
120	2438,4	1828,8	2745	4457
150	3048	2286	3440	5578
200	4064	3048	4597	7446
250	5080	3810	5754	9315
300	6096	4572	6912	11184

### WXGA / WUXGA (16:10)

인치	W (mm)	H (mm)	최단거리 (화면최대)	최장거리 (화면최소)
30	646	404	688	1135
40	862	538	928	1523
60	1292	808	1409	2298
70	1508	942	1649	2686
80	1723	1077	1889	3074
90	1939	1212	2129	3462
100	2154	1346	2369	3849
120	2585	1615	2850	4625
150	3231	2019	3570	5788
200	4308	2692	4771	7727
250	5385	3365	5972	9666
300	6462	4039	7172	11605